



**CABLE NOTES:**  
 -INTERNAL WIRES ARE 22 AWG  
 -CABLE OD IS 11.5 MM  
 -MAX BENDING RADIUS IS 3.75 in.  
 -MAX CABLE LENGTH IS 45M (150FT)  
 -CONSULT INFRANOR FOR > 25M.



ICC022-xxxRF  
 REV: B  
 INFRANOR wwwwy

ICC022-xxxRF  
 REV: B  
 INFRANOR wwwwy

DIM

1	WHT	FERRULE
2	BRN	FERRULE
3	GRN	FERRULE
4	YEL	FERRULE
5	GRY	FERRULE
6	PNK	FERRULE
7	BLU	FERRULE
8	RED	FERRULE
9	BLK	FERRULE
10	VIO	FERRULE
11	GRY/PIK	FERRULE
12	RED/BLU	FERRULE
13	WHT/GRN	FERRULE
14	BRN/GRN	FERRULE
15	WHT/YEL	FERRULE
16	YEL/BRN	FERRULE

LABEL CHART	
WIRE	LABEL
WHT	HALL U
BRN	HALL V
GRN	HALL W
YEL	A
GRY	A'
PNK	B
BLU	B'
RED	Z
BLK	Z'
VIO	GND
GRY/PNK	+5V
RED/BLU	THERM
WHT/GRN	THERM
BRN/GRN	HALL U'
WHT/YEL	HALL V'
YEL/BRN	HALL W'

**NOTES:**  
 1: THIS DRAWING IS ONLY MEANT FOR INSTALLATION PURPOSES ON AN INFRANOR MOTOR.  
 2: THIS DRAWING IS NOT TO BE RE-DISTRIBUTED OR USED TO MAKE CABLES.

ALL CABLE ASSEMBLIES MEET IPC/WHMA-A-620 CLASS 2 WORKMANSHIP AND INSPECTION STANDARDS			
DRAWN	DATE	TITLE: READY CABLE LAYOUT	
CHECKED	DATE	Infranor	
APPROVED	DATE		
PART/ASSEMBLY #		IC022-xxxRF (Encoder)	REV A
QUOTE#			
DRAWING #		SCALE NTS SIZE B SHEET 1 of 1	

UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE IN INCHES.					
CABLE OVERALL LENGTH	< 1'	> 1' - 5'	> 5' - 10'	> 10' - 25'	> 25'
TOLERANCE	+1" - 0"	+2" - 0"	+4" - 0"	+6" - 0"	+5% - 0%

A	-	DRAWING RELEASED	DATE	APPROVAL
REV	ECN	DETAILS	DATE	APPROVAL



**PROPRIETARY & CONFIDENTIAL**  
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF INFRANOR INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT WRITTEN PERMISSION FROM INFRANOR INC. IS PROHIBITED.